

5719  
RX15



Transforming articulation.



The **MQ Rammax RX1575** is an all new articulating trench roller designed to meet contractor expectations for performance and reliability. Experienced operators will appreciate the new design features that simplify operation and reduce downtime.



- **Size up your work area** with 24" or 33" working drum width options
- **Optimum compaction performance and increased stability on uneven surfaces** with the oscillating articulation joint
- **Gain traction on tough material** with steel padded drums and four sets of scrapers
- **Increased machine control** with a wireless transmitter covering a wider operational area & two ideally positioned receiver eyes
- **Easily keep the remote control battery charged** with a solar panel or cable connector
- **Be safe on the job** with our total safety concept that enables close operator proximity shut-down and infrared remote control requiring direct visual contact with receiver eyes for operation
- **Reliable starting and performance** with a powerful Yanmar engine
- **Save money on fuel** with an efficient running Yanmar diesel engine consuming up to 50% less versus leading competitors
- **No greasing required** with a maintenance free articulation joint
- **Easy access to all maintenance points** with fold-up front and rear covers

**Diesel Engine Warranty** – First two years, or up to 2,000 hours, covered by Yanmar limited warranty. Final third year, or up to 3,000 hours, covered by Multiquip limited warranty.

Specifications	RX157524	RX157533
High/Low Centrifugal Force-lbs (kn)	16,860 (75) 8,430 (37.5)	
Vibration Frequency-vpm (hz)	2,460 (41)	
High/Low Amplitude-in (mm)	0.043 (1.1) 0.024 (0.6)	
High/Low Travel Speeds-ft/min (m/min)	148 (45) 82 (25)	
Max Grade w/w-out vibration	40/50	
Inside Turning Radius-in (mm)	61 (1,541)	57 (1,436)
Outside Turning Radius-in (mm)	86 (2,191)	90 (2,286)
Engine Make/Model	Yanmar 3TNV76	
Engine Power-hp (kw)	20.4 (15)	
Operating Speed-rpm	2,400	
Diesel Fuel Tank Capacity-gal (l)	7.4 (28)	
Hydraulic Oil Tank-gal (l)	4.2 (16)	
Overall Width-in (mm)	24 (610)	33 (850)
Overall Length-in (mm)	78 (1,980)	
Overall Height-in (mm)	52 (1,317)	
Operating Weight-lbs (kg)	3,087 (1,400)	3,197 (1,450)
Wireless Remote	Infrared	
Max/Min Range of Infrared Operation-ft (m)	65 (20)/8 (2.5)	
Max/Min Range of Cable Connected Operation-ft (m)	13 (4)/8 (2.5)	
Remote Control Charging	Solar & Electric	
Cable Connector	Standard	
Shutdown Safety Bar	Optional	

Your Multiquip dealer is:

Connect with us on

